



OIL PRODUCTS

Diggers Pale Boiled Linseed Oil

DESCRIPTION

Diggers Pale Boiled Linseed Oil is a TREATED linseed oil with ADDED DRYING AGENTS to speed up drying time.

TYPICAL USES

- Timber sealer and protector for indoor furniture and cabinets
- · Wooden tool handles and sporting equipment
- Thinner for artists' oil paints
- Sealer and protective coating for concrete paths, floors, flagstones and interlocking stones

FEATURES

- Added drying agents (dries faster than Diggers Raw Linseed Oil)
- Creates a finish that is generally impervious to water, heat, scratches and most stains
- · Helps aid brushing when added to oil based paints
- Dries lighter in colour than Diggers Raw Linseed Oil

APPLICATION

Timber Protection

- 1. Clean and dry surface. Mix **Diggers Pale Boiled Linseed Oil** 50:50 with **Diggers Mineral Turpentine** for increased timber protection.
- Apply two coats with a brush, roller or spray gun. Diggers Pale
 Boiled Linseed Oil should be applied in very thin coats and rubbed
 well into the wood. It is important to allow drying time between coats.
 Clean excess oil with a clean lint free cloth to avoid the surface
 drying sticky.

How does Linseed Oil work? When linseed oil is applied to a porous surface it fills the pores and as it is exposed to the air it gels to form a protective film. The film is generally impervious to water, heat, scratches and most stains.

NOTE: Soak rags in water as spontaneous ignition may occur on drying. Dispose of rags by controlled incineration or at an approved landfill.

SAFETY

Wear suitable protective clothing, gloves and eye / face protection when using this product.

Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16406-61DIG	6 x 1 litre	9311052002050	19312852002056	112
16406-4DIG	4 x 4 litre	9311052000209	19312852002049	48
16406-20	1 x 20 litre	9312852000161	N/A	32



