

Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Araldite Super Strength Epoxy Adhesive (Class 8)

Synonyms:	Product Code	Bar Code
Araldite A + B, 1kg Kit	9300697118929	9300697118929
Araldite Super Strength, 200mL	930069710040501	9300697100405
Araldite Super Strength, 200mL	100025	9300697100405
Araldite Super Strength, 35mL	100026	9300697101396
Araldite Super Strength, 35mL	9300697101396	9300697101396
Araldite Super Strength, 24mL	930069710638400	9300697106384
Araldite Super Strength, 24mL	10027	9300697106384

Recommended use: Two pack epoxy adhesive. For bonding rigid plastics, glass, metal, china and wood.

Supplier: Selleys, a division of

DuluxGroup (Australia) Pty Ltd

ABN: 67 000 049 427

Street Address: 1956 Dandenong Road

Clayton VIC 3168

Australia

Telephone: 1300 555 205

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.

Hazard Category:

C Corrosive

Risk Phrase(s):

R34: Causes burns.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms. May cause long term adverse effects in the aquatic

environment.

Safety Phrase(s):

S1/2: Keep locked up and out of the reach of children.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

Poisons Schedule (Aust): S5

Product name: Araldite Super Strength Epoxy Adhesive (Class 8) SDS No: SELAUSEN000085

Issued: 19 June 2014 Version: 2.0 Page: 1 of 7



DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 8 Corrosive

3. COMPOSITION INFORMATION			
PART A CHEMICAL ENTITY	CAS NO.	PROPORTION	
Bisphenol A-Epichlorhydrin reaction product Bisphenol F epoxy resin Ingredients determined to be non-hazardous	25068-38-6 9003-36-5 -	> 60% 10 – 30% Balance	
		100%	
PART B CHEMICAL ENTITY	CAS NO.	PROPORTION	
Dimethylaminopropyl-1,3-propylenediamine Triethylenetetramine Ingredients determined to be non-hazardous	10563-29-8 - -	1 – 10% 1 – 10% Balance	
		100%	

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

Notes to physician: Treat symptomatically. Can cause corneal burns.

Product name: Araldite Super Strength Epoxy Adhesive (Class 8) SDS No: SELAUSEN000085

Issued: 19 June 2014 Version: 2.0 Page: 2 of 7



5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible material.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: 2X

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 36

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 8 Corrosive as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Use only in well ventilated areas. Keep containers closed when not in use.

Product name: Araldite Super Strength Epoxy Adhesive (Class 8) SDS No: SELAUSEN000085

Issued: 19 June 2014 Version: 2.0 Page: 3 of 7



Personal protection equipment: ORANGE: OVERALLS, RUBBER BOOTS, FACE SHIELD, SAFETY SHOES, GLOVES, APRON.

MANUFACTURING, PACKAGING AND TRANSPORT:

Wear overalls, face shield, elbow-length impervious gloves, splash apron and rubber boots. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

CONSUMER USE:

Wear safety glasses and gloves. Avoid inhaling vapour. Wash hands after use.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid skin and eye contact and inhalation of vapour. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Viscous liquid with an ammonia odour.

Solubility: Insoluble in water

Relative Density (20 °C): 0.95 - 1.20

Relative Vapour Density (air=1): >1 Vapour Pressure (20 ℃): N Av Flash Point (℃): >100 Flammability Limits (%): N Av Autoignition Temperature (℃): N Av % Volatile by Volume: N Av Melting Point/Range (℃): N Av Boiling Point/Range (℃): N Av **Decomposition Point (℃):** N Av N Av :Ha Viscosity: N Av Total VOC (q/Litre): N Av

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Incompatible with acids, alkalis and oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Product name: Araldite Super Strength Epoxy Adhesive (Class 8) SDS No: SELAUSEN000085

Issued: 19 June 2014 Version: 2.0 Page: 4 of 7



11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material is an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 2735

Dangerous Goods Class: 8

Packing Group: III

Hazchem Code: 2X

Emergency Response Guide No: 36

Product name: Araldite Super Strength Epoxy Adhesive (Class 8) SDS No: SELAUSEN000085

Issued: 19 June 2014 Version: 2.0 Page: 5 of 7



Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS N-(3-DIMETHYLAMINOPROPYL)-1,3-PROPYLENDIAMINE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), cyanides of Class 6, radioactive substances (Class 7) or food and food packaging in any quantity, however exemptions may apply. Note that concentrated strong acids are incompatible with concentrated strong alkalis.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 2735

Dangerous Goods Class: 8

Packing Group: III

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS N-(3-DIMETHYLAMINOPROPYL)-1,3-PROPYLENDIAMINE)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 2735

Dangerous Goods Class: 8

Packing Group: III

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS N-(3-

DIMETHYLAMINOPROPYL)-1,3-PROPYLENDIAMINE)

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

International Convention for the Prevention of Pollution from Ships (MARPOL)

Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Product name: Araldite Super Strength Epoxy Adhesive (Class 8) SDS No: SELAUSEN000085

Issued: 19 June 2014 Version: 2.0 Page: 6 of 7



16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: Revised Format change Product name change Minor Text Changes.

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Araldite Super Strength Epoxy Adhesive (Class 8) SDS No: SELAUSEN000085

Issued: 19 June 2014 Version: 2.0 Page: 7 of 7