

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **ROOF & GUTTER SILICONE SEALANT**

Recommended Use: Metal to metal sealant for steel and aluminium roofing, flashings, guttering etc.

Supplier: Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street,
 Padstow, NSW 2211
 Australia
Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825
Emergency Telephone: **1 800 033 111 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Poisons Schedule: None allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Polydimethylsiloxane compounds	70131-67-8	>60%	-
Methyl oxime silane	-	1-<10%	-
Polydimethyl siloxane	63148-62-9	1-<10%	-
Pigments	-	1-<10%	-
Amorphous silica	112945-52-5	1-<10%	-
Adhesion promoting agent	-	<5%	-
Dialkyl tin compound	-	<0.1%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Skin Contact:

Wipe excess material from skin with a clean rag or paper towel (do NOT use solvent to clean skin). Remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Safety Data Sheet

**Ingestion:**

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical assistance.

Medical attention and special treatment:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Combustible paste. On burning will emit toxic fumes.

Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up:

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage. Any residual material can be cleaned up with mineral turpentine or similar hydrocarbon solvent, or acetone based nail polish remover.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Scrape up excess material before cure. Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

7. HANDLING AND STORAGE

Conditions for safe storage:

Store in a cool, dry, well ventilated place and out of direct sunlight. Keep dry - reacts with water. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Methyl ethyl ketoxime 8 hr TWA = 3 ppm; STEL = 10 ppm *

Silica Amorphous - Precipitated silica: 8hr TWA = 10 mg/m³

Safety Data Sheet



As published by the National Occupational Health and Safety Commission.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

Engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well ventilated areas. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and safety glasses. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been removed from fingertips, nails and cuticles. Always wash hands before smoking, eating, drinking or using the toilet. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

FOR CONSUMER USE: Avoid contact with eyes and skin. Use with adequate ventilation. Wash hands after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Colour:	Coloured
Odour:	Mild
Solubility:	Insoluble in water. Uncured material is soluble in organic solvents. No solvent known for cured sealant.
Specific Gravity:	1.04 @ 20°C
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	63
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
% Volatile by Volume:	<10
Melting Point/Range (°C):	Not applicable
Boiling Point/Range (°C):	Not available
Decomposition Point (°C):	>150
pH:	Not applicable
Viscosity:	Not available
Evaporation Rate:	Not available

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid exposure to moisture. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with acids and bases .
Hazardous decomposition products:	Formaldehyde. Methyl ethyl ketoxime.
Hazardous reactions:	Reacts with moisture liberating methyl ethyl ketoxime .

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing may result in irritation to the mouth and throat. No adverse effects expected after swallowing cured (solvent free) sealant.
Eye contact:	May be an eye irritant.
Skin contact:	Repeated or prolonged skin contact may lead to irritation. Methyl ethyl ketoxime (liberated during application and setting) is a skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis in sensitive individuals. Cured sealant (solvent free) is not expected to be a skin irritant.
Inhalation:	Methyl ethyl ketoxime is liberated during application and setting. Material may be irritant to the mucous membranes of the respiratory tract (airways).

Long Term Effects:

No information available for the product.

Product Name: ROOF & GUTTER SILICONE SEALANT
Substance No: 000703517101

Issued: 03/05/2012
Version: 4

Safety Data Sheet



Toxicological Data: No LD50 data available for the product. However, for methyl ethyl ketoxime, released during sealant cure (1):

Oral LD50 (rat): 930 mg/kg (1)

For methyl ethyl ketoxime:

Negative in IN VITRO and IN VIVO genotoxicity assays. Animal studies have shown that this chemical does not cause reproductive or developmental toxicity. Four week inhalation studies in the rat produced a NOEL (for CNS effects) of 714 ppm and NOEL (for blood effects) of 283 ppm. Lifetime inhalation studies in rats and mice have observed changes to liver and nasal tissue (degeneration of olfactory epithelium). Nasal tissue changes were concentration dependant. Recent lifetime inhalation studies have shown statistically significant increase in liver tumours in male rats and male mice at 375 ppm. No tumours were present at lower concentration rates (15 and 75 ppm) or in female rats or mice at any concentration tested. Liver tumour incidence is relatively more common in rodents than humans. At current estimated exposure levels it is not anticipated that methyl ethyl ketoxime represents a carcinogenic risk to humans, however further testing is currently underway to assess the relevance of the above data to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule:

None allocated.

16. OTHER INFORMATION

(1) Material Safety Data Sheet - Australia Pty Ltd; 05/ 2007.

Safety Data Sheet



For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)
Fax: 1300 555 305 (Australia wide)
Phone: 0800 735 539 (New Zealand)
Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

5 Yearly Revised Primary SDS

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.